

SPECIFICATIONS

[PRINT](#) [EMAIL](#) [SHARE](#)

		LEGEND					
		Standard	Optional	Not Available			
Models		NV1500 S	NV1500 SV	NV2500 HD S	NV2500 HD SV	NV3500 HD S	NV3500 HD SV
POWER							
ENGINE	V6 Displacement/Liters 4L Horsepower 261 @ 5600 rpm Torque (lb-ft) - 281 @ 4000 rpm Maximum Engine Speed - 6,200 rpm Valvetrain - DOHC, Silent Chain, Two-Stage, 4-Valves per Cylinder	●	●	●	●	⊘	⊘
	V8 Displacement/Liters 5.6L Horsepower 317 @ 5200 rpm Torque (lb-ft) (V8) - 385 @ 3400 rpm Maximum Engine Speed - 6,000 rpm Valvetrain - DOHC, Silent Chain, Single-Stage, 4-Valves per Cylinder	⊘	⊘	●	●	●	●
	Recommended Regular Unleaded Fuel	●	●	●	●	●	●
	HDV1 (Fed)/LEVII-ULEV MDV6 (Cal) Emissions System	●	●	●	●	●	●
	Aluminum block and head composition	●	●	●	●	●	●
ELECTRICAL	Electronic Direct Ignition	●	●	●	●	●	●
	12-Volt Starter	●	●	●	●	●	●
	130 Amp Alternator	●	●	●	●	●	●
	Battery - 70 Amp	●	●	●	●	●	●
	Battery - 80 Amp	⊘	⊘	●	●	●	●
TRANSMISSION AND DRIVE SYSTEM	Rear-wheel Drive	●	●	●	●	●	●
	5-Speed Automatic Transmission	●	●	●	●	●	●
	V6 3.36:1 Final Drive Ratio	●	●	●	●	⊘	⊘
	V8 3.54:1 Final Drive Ratio	⊘	⊘	●	●	●	●
	Transmission Cooler	●	●	●	●	●	●
BRAKES	14.17" x 1.50" Front Vented Disc 14.37" x 1.20" Rear Vented Disc	●	●	●	●	●	●
	2-wheel Active Brake Limited Slip (ABLS)	●	●	●	●	●	●
	Electronic Brake Force Distribution	●	●	●	●	●	●
	Anti-Lock Braking System (ABS)	●	●	●	●	●	●
	Foot Parking Brake	●	●	●	●	●	●
STEERING	Engine Speed-Sensitive Hydraulic Re-Circulating Ball Steering	●	●	●	●	●	●
	45.2 Curb-to-Curb Turning Diameter (ft.)	●	●	●	●	●	●
	Manual Tilt Steering	●	●	●	●	●	●
	3-Spoke, Urethane Steering Wheel	●	●	●	●	●	●
	Bluetooth®	⊘	●	⊘	●	⊘	●
	Cruise Control	⊘	●	⊘	●	⊘	●
SUSPENSION	Front: Independent Double-Wishbone with Twin Tube Coil-Over Shocks	●	●	●	●	●	●
	Rear: Multi-leaf with Solid Axle, Twin Tube Shocks	●	●	●	●	●	●
BODY / CHASSIS	Body-on-Frame, Ladder-Type	●	●	●	●	●	●
	Corrosion-Resistant and High-Strength Steel	●	●	●	●	●	●
	Tow Bumper – Fixed-in-Bumper Type Class I – 2,000 lbs.	●	●	●	●	●	●
	Tow Hitch – 7,000 lbs. (dealer accessory)	●	●	●	●	●	●
	Tow Hitch – Class IV 9,500 pounds	⊘	⊘	●	●	●	●
	Trailer Harness (7-pin w/hard connector)	⊘	⊘	●	●	●	●
	12 Cargo Area Floor Mounting Points	●	●	●	●	●	●
	24 Cargo Area Body Side Mounting Points	●	●	●	●	●	●

LOCATE A DEALER

Enter Zip Code

go

	11 Bulkhead Mounting Points Behind 1st Row	●	●	●	●	●	●
	10 Integrated Mounting Points in Ceiling for Ladder Rack	●	●	●	●	●	●
EXTERIOR							
WHEELS & TIRES	17-inch Steel (7.5Jx17) Wheels	●	⊗	⊗	⊗	⊗	⊗
	17-inch Styled Steel (7.5Jx17) Wheels	⊗	●	●	●	●	●
	LT245/70/R17 All-Season Tires	●	●	●	●	⊗	⊗
	LT245/75/R17 All-Season Tires	⊗	⊗	⊗	⊗	●	●
	Tire Pressure Monitoring System (TPMS)	●	●	●	●	●	●
	Full Size Spare Tire, Temporary Steel Wheel Under Rear Cargo	●	●	●	●	●	●
<hr/>							
LIGHTS	Multi-Reflector Halogen Headlights	●	●	●	●	●	●
	Daytime Running Lights (DRL)	●	●	●	●	●	●
	One 10W Cargo Area Light	●	●	⊗	⊗	⊗	⊗
	Three 10W Cargo Area Lights	⊗	⊗	●	●	●	●
	Center High Mount Stop Light	●	●	●	●	●	●
<hr/>							
EXTERIOR FEATURES	Black Folding Outside Convex Mirror	●	⊗	●	⊗	●	⊗
	Black Bumper	●	⊗	●	⊗	●	⊗
	Black Door Handles	●	⊗	●	⊗	●	⊗
	Chrome Folding Outside Convex Mirror	⊗	●	⊗	●	⊗	●
	Chrome Bumper	⊗	●	⊗	●	⊗	●
	Chrome Door Handles	⊗	●	⊗	●	⊗	●
	Power Remote Controlled Outside Mirror Adjustment	⊗	●	●	●	●	●
	Rear Bumper Step	●	●	●	●	●	●
	Splash Guards	⊗	⊗	⊗	⊗	⊗	⊗
	Single Sliding Door (right hand side)	●	●	●	●	●	●
	50/50 split rear cargo doors with 243" opening feature and opening locking feature	●	●	●	●	●	●
	UV-Reducing Front Windshield Glass	●	●	●	●	●	●
	Rear Door Windows w/Privacy Glass	⊗	⊗	⊗	⊗	⊗	⊗
	Variable Intermittent Wipers	●	●	●	●	●	●
	Integrated Roof Rack Mounting Points (10 for Standard Roof, 8 for High Roof)	●	●	●	●	●	●
	Roof Load Weight Rating: 500 lbs. Maximum for Standard Roof, 300 lbs. Maximum for High Roof	●	●	●	●	●	●
<hr/>							
INTERIOR							
SEATING & CARGO AREA	2-Passenger Capacity	●	●	●	●	●	●
	Seats with Premium Cloth with Water-Repellent Feature and Wear-Resistant Patches	●	●	●	●	●	●
	4-Way Manual Driver Seat	●	⊗	●	⊗	●	⊗
	8-Way Power Lumbar Driver Seat	⊗	●	⊗	●	⊗	●
	Manual Lumbar Seat	⊗	●	⊗	●	⊗	●
	4-Way Manual Passenger Seat	●	●	●	●	●	●
	Fold-Down Passenger Seat	●	●	●	●	●	●
	TPO (Thermoplastic PolyOlefin) Front Row Floor Covering	●	●	●	●	●	●
<hr/>							
AUDIO & NAVIGATION	2-Din AM/FM/CD w/Aux, 2 Speakers	●	⊗	●	⊗	⊗	●
	2-Din AM/FM/CD/MP3 w/Aux, 4 Speakers, RDS	⊗	●	⊗	●	⊗	●
	XM® Satellite Radio	⊗	⊗	⊗	⊗	⊗	⊗
	Bluetooth® Hands-free Phone System	⊗	⊗	⊗	⊗	⊗	⊗
	Secure Data Card-Based Navigation System with 5.0-Inch Touch Screen Display	⊗	⊗	⊗	⊗	⊗	⊗
<hr/>							
INSTRUMENTATION	Analog Meter Gauges • Speedometer – MPH main, KPH sub	●	●	●	●	●	●

	<ul style="list-style-type: none"> Tachometer Coolant Temperature Fuel Level 						
	<ul style="list-style-type: none"> Digital Meter Gauges Twin trip odometer Clock Engine oil pressure Voltmeter Transmission oil temperature - 	●	●	●	●	●	●
	Tire Pressure Monitoring System (TPMS)						
COMFORT & CONVENIENCE							
	Cruise Control w/ Steering Mounted Controls	⊗	●	⊗	●	⊗	●
	Power Windows – Driver's One-Touch Auto Down	⊗	●	⊗	●	⊗	●
	Power Door Locks Selective Unlocking and Anti-Lockout	⊗	●	⊗	●	⊗	●
	Remote Keyless Entry System	⊗	●	⊗	●	⊗	●
	Center Console w/ <ul style="list-style-type: none"> Sliding table Lockable storage Coin holder Dedicated storage for trash box 	⊗	⊗	●	●	●	●
	PC and battery, clipboard, filing folders						
	Full-length 1st Row Overhead Storage Console and Individual Map Lights (High-Roof ONLY)	⊗	⊗	●	●	●	●
	2 Front Map Lights	●	●	●	●	●	●
	Air Conditioning/Heater Manual Temperature Control	●	●	●	●	●	●
	Front Window Defogger	●	●	●	●	●	●
	Rear Door Glass Defogger	⊗	⊗	⊗	⊗	⊗	⊗
	2 Cup Holders in Lower Dash	●	●	●	●	●	●
	2 Cup Holders in Center Console	⊗	⊗	●	●	●	●
	Bottle Holders in Front Doors	●	●	●	●	●	●
	One 12V Power Outlet in Instrument Panel	●	●	●	●	●	●
	One 12V Power Outlet in Center Console	⊗	⊗	●	●	●	●
	Two 120V Power Outlets – Center Console and Rear Driver's Side D-Pillar	⊗	⊗	⊗	●	⊗	●
	A-Pillar Assist Grips	●	●	●	●	●	●
	Sliding Door B-Pillar Assist Grips	●	●	●	●	●	●
	Driver's Side Rear Cargo Door Assist Grips	⊗	●	⊗	●	⊗	●
	Passenger Side Rear Cargo Door Assist Grips	●	●	●	●	●	●
	Inside Rearview Mirror (with Rear Windows)	⊗	⊗	⊗	⊗	⊗	⊗
	RearView Monitor	⊗	⊗	⊗	⊗	⊗	⊗
	Rear Sonar System	⊗	●	⊗	●	⊗	●
SAFETY & SECURITY							
PASSENGER RESTRAINT SYSTEM							
	Dual-Stage Front Air Bags	●	●	●	●	●	●
	Driver and Front Seat-Mounted Side Impact Air Bags	⊗	⊗	⊗	⊗	⊗	⊗
	Roof-Mounted Curtain Side-Impact Air Bags	⊗	⊗	⊗	⊗	⊗	⊗
	3-Point Height-Adjusting w/Pre-tensioners and Load Limiters Front Outboard Seatbelts	●	●	●	●	●	●
PASSIVE SAFETY							
	Energy-Absorbing Steering Column	●	●	●	●	●	●
	Zone Body Construction with Front Crumple Zones and Rear Crumple Zones	●	●	●	●	●	●
	Side-Door Guard Beams	●	●	●	●	●	●
	Shift Interlock System	●	●	●	●	●	●
	Vehicle Dynamic Control (VDC) with Traction Control System (TCS)	●	●	●	●	●	●
	Tire Pressure Monitoring System (TPMS)	●	●	●	●	●	●
SAFETY & SECURITY SYSTEMS							
	Immobilizer	⊗	●	⊗	●	⊗	●
	Vehicle Security System with Alarm	⊗	●	⊗	●	⊗	●
	Steering wheel locks when key is removed	●	●	●	●	●	●
	Vehicle Dynamic Control (VDC)	●	●	●	●	●	●
	Traction Control System	●	●	●	●	●	●
DIMENSIONS							

EXTERIOR (inches)	146.1" Wheelbase	●	●	●	●	●	●
	240.6" Overall Length	●	●	●	●	●	●
	79.9" Width (without mirrors)	●	●	●	●	●	●
	83.9" Standard Roof Height	●	●	●	●	⊗	⊗
	84.9" Standard Roof Height	⊗	⊗	⊗	⊗	●	●
	105.0" High Roof Height	⊗	⊗	●	●	⊗	⊗
	106.0" High Roof Height	⊗	⊗	⊗	⊗	●	●
	61.6" Rear Door Max. Opening	●	●	●	●	●	●
	8.1" Minimum Ground Clearance (Stationary)	●	●	●	●	●	●
	Step-In Height • 18.0" Front Door • 19.4" Side Door • 19.8" Rear Doors	●	●	●	●	⊗	⊗
	Step-In Height • 18.7" Front Door • 20.2" Side Door • 20.9" Rear Doors	⊗	⊗	⊗	⊗	●	●
	Approach Angle - 17.5°	●	●	●	●	●	●
	Departure Angle - 17.4°	●	●	●	●	●	●
	Breakover Angle - 16.3°	●	●	●	●	●	●
INTERIOR (inches)	42.8" Standard Roof Head Room	●	●	●	●	●	●
	63.6" High Roof Head Room	⊗	⊗	●	●	●	●
	42.0" Leg Room	●	●	●	●	●	●
	60.6" Hip Room	●	●	●	●	●	●
	65.7" Shoulder Room	●	●	●	●	●	●
CARGO AREA (inches)	120.0" Maximum Length	●	●	●	●	●	●
	121.9" Maximum Cargo Length Behind Center Console at Vehicle Center	⊗	⊗	●	●	●	●
	150.4" Maximum Cargo Length Without Center Console at Vehicle Center	●	●	●	●	●	●
	70.2" Maximum Width	●	●	●	●	●	●
	54.3" Maximum Width Between Rear Wheel Houses	●	●	●	●	⊗	⊗
	55.8" Maximum Roof Height – Standard Roof	●	●	●	●	●	●
	76.9" Maximum Roof Height – High Roof	⊗	⊗	●	●	●	●
WEIGHTS - STANDARD ROOF	Curb (lbs) - V6	5791	5853	5810	5903	⊗	⊗
	Curb (lbs) - V8	⊗	⊗	5873	5966	5878	5971
	Weight Distribution (%) Front/Rear - V6	53/47	52/48	53/47	52/48	⊗	⊗
	Weight Distribution (%) Front/Rear - V8	⊗	⊗	53/47	53/47	53/47	53/47
WEIGHTS - HIGH ROOF	Curb (lbs) - V6	⊗	⊗	5973	6066	⊗	⊗
	Curb (lbs) - V8	⊗	⊗	6046	6139	6050	6143
	Weight distribution (%) Front/Rear - V6	⊗	⊗	52/48	52/48	⊗	⊗
	Weight distribution (%) Front/Rear - V8	⊗	⊗	53/47	53/47	52/48	52/48
CAPACITIES	28.0 Gallons Fuel - V6 & V8	●	●	●	●	●	●
	5.4 Quarts Oil – V6	●	●	●	●	⊗	⊗
	6.5 Quarts Oil – V8	⊗	⊗	●	●	●	●
	10.7 Quarts Coolant V6 & V8	●	●	●	●	●	●
	9500 lbs Towing (Max. cap. properly equipped with factory option tow hitch) - V8 ONLY (N/A V6)	⊗	⊗	⊗	⊗	⊗	⊗
	7000 lbs Towing (Max. cap. properly equipped w/ dealer accessory tow hitch) – V6 & V8	⊗	⊗	⊗	⊗	⊗	⊗
PAYLOAD (lbs)	Standard Roof - V6	2590	2535	3141	3031	⊗	⊗
	Standard Roof - V8	⊗	⊗	3086	2976	3925	3747

	High Roof - V6	⊗	⊗	2921	2866	⊗	⊗
	High Roof - V8	⊗	⊗	2866	2755	3637	3582
VOLUME (Cubic Feet)	299.7 EPA Total Volume – Standard Roof	●	●	●	●	●	●
	420.5 EPA Total Volume – High Roof	⊗	⊗	●	●	●	●
	68.3 Interior Passenger Volume – Standard Roof	●	●	●	●	●	●
	101.5 Interior Passenger Volume – High Roof	⊗	⊗	●	●	●	●
	234.1 EPA Cargo Volume – Standard Roof	●	●	●	●	●	●
	323.1 EPA Cargo Volume – High Roof	⊗	⊗	●	●	●	●
EPA FUEL ECONOMY	EPA Classification	Conventional Van	Conventional Van	Conventional Van	Conventional Van	Conventional Van	Conventional Van